

### **DAIMLERCHRYSLER CORPORATION**

**EXECUTIVE ORDER A-009-0693** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		(*=N/A ( A/E=e	RMEDIATE I-USE PLIANCE or full in-use; exh. / evap. diate in-use)	FUEL TYPE	
2006	6CRXT04.76U0	MDV: 5751-8500 Pounds ALVW	USEPA Bin 10a (OPT)	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2	
2006			Counted as ARB ULEV	120K	150K	*	E	Unleaded)	
No.	ECS &	SPECIAL FEATURES	EVAPORATIVE	DISPLACEMENT (L)					
1	2TWC, 2H	02S(2), SFI, EGR, OBD(P)	6CRXR0						
*		*	6CRXR0						
*		*			•	<b>1.</b> 7			
*		*		*					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>0</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_

Allen Lyons, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# **ATTACHMENT**

## **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAGE [g/ml]			NMOG @ RAF=* CH4 RAF = *		CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram										
CERT STD		NMOG CERT	NMHC CERT	NMHC	mi=mile;	K=1000 miles D [g/mi]	; F=degree	es Fahrenhe Ox [g/mi]	it; SFTP=s	upplementa CHO [mg/1	l federal t	est procedure PM [g/	9	-	ogram Ox [g/ml]
•		[g/mi]	[g/mi]	[g/mi]	CERT		CER				TD	CERT	STD	CERT	STD
HE LO	@ 50K	0.109	*	0.195	1.5	4.4	0.1	0.4		1	8.	*	*	0.04	0.53
40000000000000000000000000000000000000	@ UL	0.109	*	0.280	1.5	6.4	0.1	0.6	*	2	7.	*	*	0.04	0.80
	0 50°F & 4K	*	•	*	*	. *	*	*	*	·	•	*	*	*	•
	g/mi)		NMHC+NO (compo					NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
@ 20°F	& 50K			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	5.8	SFTP @ 4	000 miles	*	*	*	*	0.2	0.6	3.6	11.8	0.10	0.44	0.7	4.0
STD	12.5	SFTP	@ 120000 miles	0.29	1.67	*	*	*	*	7.4	19.3	*	*	2.4	6.4
						rnal + Hot Soak s/test) @ UL		Running Loss (grams/mile) @ UL					efueling Vapor ms/gallon) @ UL		
		ST	ď	CERT	;	STD	CER	т	STD		CERT		STD		
6CRXR0218GTH 0.53		0.53	0.9	90	0.46		1,15	0.00	1	0.05		0.08		0.20	
60	CRXR0283G	TH	0.40	0.9	90	0.33		1.15	0.00	0	0.05		0.04	-	0.20

\* = not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=utra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

### 2006 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. Intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
DODGE	DURANGO 4WD	6CRXR0218GTH	11	4.7	*	E	SFTP	Partial
DODGE	RAM 1500 PICKUP 2WD	6CRXR0218GTH	1	4.7	*	E	SFTP	Partial
DODGE	RAM 1500 PICKUP 2WD	6CRXR0283GTH	1	4.7	*	E	SFTP	Partial
DODGE	RAM 1500 PICKUP 4WD	6CRXR0218GTH	1	4.7	*	E	SFTP	Partial
DODGE	RAM 1500 PICKUP 4WD	6CRXR0283GTH	1	4.7	*	E	SFTP	Partial